



SAFETY DATA SHEET

EPOXY FLOOR COATING EP40 BASE GREY

Revision 1
Revision date 25-Feb-2009

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name EPOXY FLOOR COATING EP40 BASE GREY
Company Wykamol Group Limited
Unit 3, Boran Court
Network 65 Business Park
Hapton, Burnley
Lancashire. BB11 5TH
sales@wykamol.com www.wykamol.com
Telephone 0845 400 6666
Emergency telephone number 0845 400 6666

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Bisphenol A-(epichlorhydrin) (reaction product)	30-40%	25068-38-6	500-033-5	Xi; R36/37/38 R43 N; R51/53

3. HAZARDS IDENTIFICATION

Main hazards Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

Skin contact Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Eye contact Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Inhalation Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon oxides.
Fire hazards Burning produces irritating, toxic and obnoxious fumes.
Protective equipment Wear suitable respiratory equipment when necessary.

EPOXY FLOOR COATING EP40 BASE GREY

Revision 1
Revision date 25-Feb-2009

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Store in a cool, well ventilated place away from foodstuffs. Keep containers sealed until mixing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Grey.
Odour	Mild.
Boiling point	100°C
Flash point	> 200°C
Vapour pressure	2.3 pKa
Relative density	1.35
Water solubility	miscible in water.
Viscosity	< 1 Pa.s

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information

EPOXY FLOOR COATING EP40 BASE GREY Oral Rat LD50 = > 15000 mg/kg

Acute toxicity	May cause sensitisation by skin contact.
-----------------------	--

12. ECOLOGICAL INFORMATION

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--------------------	---

EPOXY FLOOR COATING EP40 BASE GREYRevision 1
Revision date 25-Feb-2009**13. DISPOSAL CONSIDERATIONS**

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Do NOT reuse empty containers.

14. TRANSPORT INFORMATION**ADR/RID**

UN 3082	Packing group III
Class 9	Hazard ID 90
Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., .

IMDG

UN 3082	Packing group III
Class 9	Marine pollutant .
EmS Code F-A S-F	

IATA

UN 3082	Packing group III
Class 9	Subsidiary risk -
Packing Instruction 914 (Cargo)	Maximum quantity 450 L
Packing Instruction 914 (Passenger)	Maximum quantity 450 L

Further information The product is not classified as dangerous for carriage.

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xi - Irritant; N - Dangerous for the environment



Risk phrases R36/38 - Irritating to eyes and skin.
R43 - May cause sensitisation by skin contact.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases S24 - Avoid contact with skin.
S29 - Do not empty into drains.
S37 - Wear suitable gloves.

EPOXY FLOOR COATING EP40 BASE GREY

Revision 1
Revision date 25-Feb-2009

16. OTHER INFORMATION

Text of risk phrases in Section 2

R36/37/38 - Irritating to eyes, respiratory system and skin.

R43 - May cause sensitisation by skin contact.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.



SAFETY DATA SHEET

EPOXY FLOOR COATING EP 40 HARDENER

Revision 0
Revision date 25-Feb-2009

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name EPOXY FLOOR COATING EP 40 HARDENER
Company Wykamol Group Limited
Unit 3, Boran Court
Network 65 Business Park
Hapton, Burnley
Lancashire. BB11 5TH
sales@wykamol.com www.wykamol.com
Telephone 0845 400 6666
Emergency telephone number 0845 400 6666

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients	Conc.	CAS	EINECS	Symbols/Risk phrases
3,6,9,12-Tetra-azatetradecamethylenediamine	1 - 10%	4067-16-7	223-775-9	C; R34 R43 N; R50/53

3. HAZARDS IDENTIFICATION

Main hazards May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

Skin contact Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Eye contact Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Inhalation Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon oxides.
Fire hazards Burning produces irritating, toxic and obnoxious fumes.
Protective equipment Wear suitable respiratory equipment when necessary.

EPOXY FLOOR COATING EP 40 HARDENER

Revision 0
Revision date 25-Feb-2009

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Store in a cool, well ventilated place away from foodstuffs. Keep containers sealed until mixing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Yellow.
Odour	Ammoniacal.
Boiling point	100°C
Vapour pressure	2.3 kPa
Relative density	1.02
Water solubility	miscible in water.
Viscosity	< 1 Pa.s
Autoignition temperature	> 150 °C

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information

EPOXY FLOOR COATING EP 40 HARDENER Oral Rat LD50 = > 5000 mg/kg

Acute toxicity	May cause sensitisation by skin contact.
-----------------------	--

12. ECOLOGICAL INFORMATION

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--------------------	---

EPOXY FLOOR COATING EP 40 HARDENERRevision 0
Revision date 25-Feb-2009**13. DISPOSAL CONSIDERATIONS**

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Do NOT reuse empty containers.

14. TRANSPORT INFORMATION**ADR/RID**

UN 3082	Packing group III
Class 9	Hazard ID 90
Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., .

IMDG

UN 3082	Packing group III
Class 9	Marine pollutant .
EmS Code F-A S-F	

IATA

UN 3082	Packing group III
Class 9	Subsidiary risk -
Packing Instruction 914 (Cargo)	Maximum quantity 450 L
Packing Instruction 914 (Passenger)	Maximum quantity 450 L

Further information The product is not classified as dangerous for carriage.

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xi - Irritant; N - Dangerous for the environment



Risk phrases R43 - May cause sensitisation by skin contact.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases S24 - Avoid contact with skin.
S29 - Do not empty into drains.
S37 - Wear suitable gloves.

EPOXY FLOOR COATING EP 40 HARDENER

Revision 0
Revision date 25-Feb-2009

16. OTHER INFORMATION

**Text of risk phrases in
Section 2**

R34 - Causes burns.

R43 - May cause sensitisation by skin contact.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.