



SAFETY DATA SHEET

Page 1 of 3

FILLET SEAL

Revision 0
Revision date 20-Feb-2009

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name FILLET SEAL

Company Wykamol Group Limited
Unit 3, Boran Court
Network 65 Business Park
Hapton, Burnley
Lancashire. BB11 5TH
sales@wykamol.com www.wykamol.com

Telephone 0845 400 6666

Emergency telephone number 0845 400 6666

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Ordinary Portland Cement (Portland cement respirable dust)	40 - 50%	65997-15-1		Xi; R38-43

3. HAZARDS IDENTIFICATION

Main hazards Irritating to skin. May cause sensitisation by skin contact.

4. FIRST AID MEASURES

Skin contact Causes burns. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention.

Inhalation Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.

Ingestion Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO₂), dry chemical, foam.

Fire hazards Corrosive. Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

Print date 20-Feb-2009

FILLET SEAL

Revision 0
Revision date 20-Feb-2009

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Ordinary Portland Cement (Portland cement respirable dust)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 4 WEL 15 min limit mg/m3: -
---	--	--

Ordinary Portland Cement (Portland cement total inhalable dust)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: -
--	--	---

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Self-contained breathing apparatus.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Powder.
Colour	Grey.
Odour	Odourless.
pH	11.0 - 13.5
Relative density	1.4

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information	There is no data available on the product itself. The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within the General Directive on Preparations (88/37/EEC).
Corrosivity	Causes burns.

12. ECOLOGICAL INFORMATION

Ecotoxicity	The unused product is a minor water pollutant. Large quantities may be toxic to fish. Do not empty into drains.
--------------------	---

FILLET SEAL

Revision 0
Revision date 20-Feb-2009

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.

14. TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
---------------------	--

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xi - Irritant



Risk phrases R38 - Irritating to skin.
R43 - May cause sensitisation by skin contact.

Safety phrases S24 - Avoid contact with skin.
S37 - Wear suitable gloves.

16. OTHER INFORMATION

Text of risk phrases in Section 2 R38 - Irritating to skin.
R43 - May cause sensitisation by skin contact.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.