



# Permanent Pothole Repair

## Permanent Pothole Repair Solution

### Applications

Ultracrete Permanent Pothole Repair is a suitable solution for roads, pavements, driveways and car parks. The product can be trafficked instantly in wet, freezing and hot conditions and at the same time is compatible with the existing road surface. Ultracrete Permanent Pothole Repair can be applied at depths of 20mm – 100mm. (Greater depths can be achieved by applying the layer-on-layer method.)

### Technical

Ultracrete Permanent Pothole Repair includes fully graded, high PSV interlocking aggregate and specially formulated bitumen and is supplied in recyclable 25kg containers.

### Application

Pothole repairs can be achieved at any depth.

1. Ensure pothole is free of debris and standing water.
2. Apply Ultracrete SCJ spray sealant to pothole edges.
3. Apply the product slightly proud of the pothole.
4. Compact with a hand tamper, or suitable mechanical alternative.

### Health & Safety

The binder used in Ultracrete PPR is particularly tenacious. Ensure that protective gloves, overalls and protective footwear are worn at all times while handling the material. Avoid skin contact. However, should the bitumen binder adhere to the skin it can be removed with soap and water. Seek medical advice if discomfort continues. If product comes into contact with the eyes rinse with plenty of water and seek medical advice. For full updated Material Safety Data Sheet please visit [www.instarmac.co.uk](http://www.instarmac.co.uk)



### Features & Benefits

- 3mm grade stone
- Used in wet, freezing and hot conditions
- No special preparation
- Instant trafficking
- Only one visit required
- Recyclable containers
- Compatible with flexible road surfaces
- Solvent free
- Ready to use – No need to add water
- Polished stone value 60 psv
- Absolutely no waste
- Environmentally friendly – No CO<sub>2</sub> gases



Used by Local Authorities and major contractors for over 30 years



Made in the UK



# Permanent Pothole Repair

## Permanent Pothole Repair Solution

### Physical Properties

	PSV	Colour	Unit/Packaging
3mm Dense Mix	60	Black	25kg Plastic Containers



### Product Details

Storage	Store in a cool and well-ventilated place.
Shelf Life	Shelf life in correct conditions for sealed goods is 6 months.
Coverage	1m <sup>2</sup> x 15mm (compacted).
Handling Guidelines	Ultracrete Permanent Pothole Repair is manufactured and delivered within as short a time as possible to ensure fresh easy to lay material is supplied. It should be noted that tubs on pallets, particularly those at the bottom, could appear firm. Applying light pressure to the edge of the bag will restore the material to its normal consistency.

### Contact Us

**Instarmac® Group plc**, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466

Email: [email@instarmac.co.uk](mailto:email@instarmac.co.uk) Order: [orders@instarmac.co.uk](mailto:orders@instarmac.co.uk) Website: [www.instarmac.co.uk](http://www.instarmac.co.uk)

Ultracrete products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.