Total Wall Care®

Colour Matching Injection Mortar

DESCRIPTION

Total Wall Care Colour Matching Injection Mortar is a combination of purely mineral mortar and natural or synthetic pigments. It has been specially formulated for repairing crack ranging from 3mm to 10mm. It contains no latex or acrylic bonding agents or additives, and is vapour permeable for compatibility with masonry substrates.

INSTRUCTIONS & NOTES

Please refer to detailed instruction leaflet inside tub.

Mix 2 to 2.5 parts dry mortar with 1 part water. For a minimum of 3 minutes. Mix by hand or with a slow speed drill with a mixing paddle until smooth. Pour mixed mortar into syringe and replace lid on tub.

Ensure surface to be repaired is free from dust, dirt and loose particles. Loose and crumbling material should be lightly brushed away. Substrate should be pre-moistened and damp but not too wet. For deep cracks attach extension tube to syringe. Starting from the bottom of the crack inject the mortar leaving 3-5mm proud of the surface.

Product should not be applied in temperatures below 5°C or above 32°C.

The tools used for applying the Brick Repair Mortar can be cleaned with clear water.

Any spatters in undesired places should be removed with clear water.

TECHNICAL CHARACTERISTICS		SAFETY INFORMATION
Specific Gravity (Kg/dm ³ Compression Strength (N/mm ² : Water Mixing Factor (ml/Kg) Volume mixed mortar (ml/Kg) Consumption (Kg/m ² , 15mm thickness)	1.9 64.5 -70.0 350 - 400 700 1.5	 Keep Out of Reach of Children Irritating to eyes and skin Avoid contact with eyes and skin Risk of serious damage to eyes In case of contact with eyes and skin rinse immediate with plenty of water and seek medical advice Do not breathe dust
STORAGE		• If swallowed seek medical advice immediately and sl this label or container
Can be stored for a maximum period of 24 months, provided the material is stored in sealed packing, in a dry, cool and frost proof place.		• Gloves and eye protection should be worn during mix and application.