

MATERIAL SAFETY DATA SHEET

November 2005
Revision 03

The Wykamol Group,
Units 1-3, Knowsley Road Industrial Estate,
Knowsley Road, Haslingden, Lancs, BB4 4RX

Tel: 01706 831223

Fax: 01706 214998

1. PRODUCT IDENTIFICATION

Trade Name	ULTRACURE
Description	Masonry Damp Proof Course Cream

2. HAZARDOUS INGREDIENTS

Component	% / w/w	Hazard Data (EEC Classification)
White Mineral Oil	50<75%	Xn CAS No. 92062-35-6
Siloxane and Alkylalkoxysilane	15%	Xi, N

3. HAZARD IDENTIFICATION

This product is not classified under the Chemicals (Hazard Information and Packaging) regulations 2002)

6. HANDLING AND STORAGE

Handling: Wear rubber gloves and safety glasses or goggles.

Storage: Keep containers sealed and store above 5°C.

4. EMERGENCY & FIRST AID

Eyes: Wash copiously with water or eye wash for at least 15 minutes. If symptoms persist, seek medical attention.

Skin: Remove contaminated clothing.
Wash affected skin with soap and plenty of water.

Inhalation: Remove to fresh air.

Ingestion: Rinse out mouth and then drink plenty of water. Consult doctor as soon as possible. Keep the person affected quite.

7. EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures: Use only in well ventilated areas.

Personal Protection: Coveralls, chemically resistant footwear and synthetic rubber/PVC gloves.

Eye Protection: Goggles giving full eye protection.

Respiratory Protection: Not normally required.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Water mist, alcohol foam, carbon dioxide or dry chemical.

Special Fire Fighting Procedures: None

Unusual Fire Hazards: Collect contaminated fire fighting water separately. It must not enter drains. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

8. SPILL OR LEAK PROCEDURES

Do not allow to enter drains or sewers. Contain and absorb onto earth or sand and sweep up. Dispose of in accordance with local regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	white cream	Odour	none
pH	-	Boiling Point	-
Melting Point	-	Flash Point	> 100°C
Self -inflammability	product is not self-igniting	Autoignition Temp.	-
Oxidising Properties	-	Solubility in Water	Fully miscible
Relative Density @ 20°C	0.86 g/cm ³	Vapour Pressure	-

10. STABILITY AND REACTIVITY

<p>Conditions to avoid: Avoid working in confined spaces with poor ventilation.</p>
<p>Materials to avoid: Avoid any strong acids and strong bases.</p>
<p>Hazardous decomposition products:</p> <p>None if used properly. None if stored properly. In the long term ethanol is formed by hydrolysis.</p>

11. TOXICOLOGICAL INFORMATION

<p>Inhalation: Alkoxy silane: Do not inhale aerosol mist because of the risk of lung damage.</p>
<p>Skin Contact: No irritating effect.</p>
<p>Skin Absorption: -</p>
<p>Eye Contact: No irritating effect.</p>
<p>Ingestion: No acute oral data available.</p>
<p>Acute Overexposure: -</p>
<p>Chronic Overexposure: -</p>

12. ECOLOGICAL INFORMATION

<p>Biodegradability: Product hydrolyses to ethanol, silanol and/or siloxanol compounds.</p> <p>Aquatic Toxicity: Considered to be a weak water pollutant.</p>

13. WASTE DISPOSAL

<p>Disposal through an authorised contractor to an incinerator site. In accordance with the Control of Pollution Act 1974. Control of pollution (Special Waste) Regulations 1980 apply. Hazardous waste as defined by EC Council Directive 91/689/EEC. Disposal outside the UK in accordance with local regulations governing hazardous liquid and solid wastes.</p>

14. TRANSPORT INFORMATION

<p>Packaging:- 1.0 litre & 400ml cartridge and 3.0 litre pail.</p> <p>Not classified as hazardous for transport purposes.</p>

15. REGULATORY INFORMATION

<p>The COSHH Regulations 2002 may apply to the use of this product at work.</p>

16. OTHER INFORMATION

<p>BWPDA DP6 : Safety in damp proofing.</p>
