



SPRAYABLE TIMBERCARE

LAN TECH – 01/2007

**PERMANENT
STABLE COLOUR**

**QUICK & EASY
TO APPLY**

**WATER REPELLENT
COATING**

DESCRIPTION:

SPRAYABLE TIMBERCARE is a water-based surface coating formulated for use on all types of rough-sawn garden timbers to give a durable, weatherproof and colour stable finish to sheds, fence panels, gates, posts, trellis, troughs, pots and edge trims. SPRAYABLE TIMBERCARE is formulated especially to suit a SPRAY APPLIED application using a portable “garden type” spray pack to give a fast and even application across all rough sawn timber surfaces. Its’ UV resistant pigments provide long lasting protection and colour retention, which along with excellent water repellent activity to prevent the ingress of moisture ensures the long-term protection for all treated areas of the timber structure. This easy to apply, sprayable formulation allows for rapid and convenient reaching into all areas & profiles and achieving an even consistent finish within a much shorter timescale.

PREPARATION:

SPRAYABLE TIMBERCARE can be used on new or bare timbers, or over previously treated decking stained with a similar colour. It is important to ensure that all timbers have been previously pre-treated with an approved wood preservative to ensure protection against wood destroying fungi. All exposed decking surfaces should be dry and free from dirt, dust, mould, algae and any loose, or flaking previous coatings likely to inhibit the decking stain from direct contact with the timber surface. The use of LANGLOW ABICIDE fungicidal wash is recommended to ensure all surfaces are adequately prepared particularly on established and exposed garden structures.

APPLICATION:

Do not apply in wet or damp / humid conditions, at temperatures below 10°C or when rain is likely before product can dry. Stir the contents of this container thoroughly before use to ensure a smooth, consistent and free-flowing liquid. Apply using the recommended hand pumped fine sprayer pack and ensure the unit has been thoroughly flushed through with clean water to remove any fine particles or blockages. Ensure the container is consistently pressurised to its’ recommending operating level and adjust nozzle to ensure a broad fine spray mist is achieved and hold the nozzle end no more than 20cm from the timber surface, spraying along the line of the grain. Make sure all end grains and sides of timbers are thoroughly coated to ensure maximum protection. In ideal conditions allow at least 4 hours drying time before applying a second coat if a deeper colour is needed to hide a previously applied stain treatment. When the application is complete, thoroughly wash brushes in warm soapy water to preserve them for future use. Avoid applying when rainfall is forecast or when there is a breeze sufficient to deflect the spray mist and ensure all surrounding structures are protected from accidental contact with the spray applied stain as it will be difficult to remove especially from porous masonry.

COVERAGE:

Depending upon the surface texture, age and porosity of the timbers, the coverage of SPRAYABLE TIMBERCARE will vary accordingly. On rough sawn timbers and porous exposed end grains this product will cover at between 3 to 4 square metres per litre, per coat, however on smoother timber surfaces coverage rates of up to 5 square metres per litre per coat may be achieved. Drying rate will be influenced by weather conditions and moisture content of the timber. Avoid application to wet timbers, in cool conditions and when rain is likely. In ideal conditions each coat will be touch dry in about 4 hours however allow up to 24 hours in cool humid weather.

HEALTH & SAFETY:

Keep out of reach of children. Ensure good ventilation during application and drying. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of soap and water or a recognised skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice. May be Harmful if swallowed. This product and its’ container must be disposed of in a safe way. Local authorities have special facilities for the disposal of waste coatings. Do not empty into drains, watercourses or access routes to septic tanks.

STORAGE & PACKAGING:

SPRAYABLE TIMBERCARE is available only in 5 litre polypropylene containers. Store in cool, well-ventilated conditions away from direct sources of heat or ignition. Should further more specific technical information be required, contact the Palace Technical helpline on 0151 486 6101.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company’s terms and conditions of sale, copies of which are available on request.

PALACE CHEMICALS Ltd
Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB
Tel: 0151 486 6101 – Fax: 0151 448 1982
e-mail technical@palacechemicals.co.uk