

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : CRACK SEALER PLUS BASE
 Product code : CRACKBASE/GREY/RED

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use, Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wykamol Group Ltd.
 Unit 3. Boran Court. Network 65 Business Park.
 Hapton, Burnley BB11 5TH - United Kingdom
 T +44 (0) 1282 473100
info@wykamol.com - www.wykamol.com

1.4. Emergency telephone number

Emergency number : +44 (0) 1282 473100 (0800 - 1700 UK time)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Muta. 1B	H340
Carc. 1B	H350
STOT RE 2	H373
Aquatic Chronic 2	H411

Full text of H-phrases: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Stoddard solvent, Low boiling point naphtha - unspecified, [A colorless, refined petroleum distillate that is free from rancid or objectionable odors and that boils in a range of approximately 148.8°C to 204.4°C. (300°F to 400°F).], oxirane, mono[(C12-14-alkyloxy)methyl] derivs., reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700), Formaldehyde, oligomeric reaction products

Hazard statements (CLP) :

H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H340 - May cause genetic defects
 H350 - May cause cancer
 H373 - May cause damage to organs through prolonged or repeated exposure
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P260 - Do not breathe fume, vapours
 P264 - Wash hands, forearms and face thoroughly after handling
 P280 - Wear eye protection, protective clothing, protective gloves
 P302+P352 - IF ON SKIN: Wash with plenty of water

CRACK SEALER PLUS BASE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	50 - 80	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS No) 68609-97-2 (EC no) 271-846-8 (EC index no) 603-103-00-4	5 - 50	Skin Irrit. 2, H315 Skin Sens. 1, H317
Formaldehyde, oligomeric reaction products	(CAS No) 9003-36-5	5 - 50	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Stoddard solvent, Low boiling point naphtha - unspecified, [A colorless, refined petroleum distillate that is free from rancid or objectionable odors and that boils in a range of approximately 148.8°C to 204.4°C. (300°F to 400°F).]	(CAS No) 8052-41-3 (EC no) 232-489-3 (EC index no) 649-345-00-4	< 5	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304 STOT RE 1, H372

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8	(C \geq 5) Eye Irrit. 2, H319 (C \geq 5) Skin Irrit. 2, H315

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

CRACK SEALER PLUS BASE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing fume.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from children. Keep container closed when not in use. : Keep away from
- Incompatible products : Keep away from. Oxidizing agent. Strong acids. Strong bases.
- Storage temperature : 5 - 35 °C

7.3. Specific end use(s)

See technical instructions for use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure.
- Materials for protective clothing : Wear suitable protective clothing and gloves
- Hand protection : Wear protective gloves
- Eye protection : Chemical goggles or safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : Wear appropriate mask
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Paste.
- Colour : Grey. red.
- Odour : slight. Sweet.
- Odour threshold : No data available
- pH : No data available

CRACK SEALER PLUS BASE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable
Vapour pressure	: > 0,1 mbar At 25 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,08 g/ml At 25 °C
Solubility	: Insoluble.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 1300 mPa.s At 25 °C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

amines. Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
LD50 oral rat	11400 mg/kg
LD50 oral	15600 mg/kg mouse
LD50 dermal rabbit	> 20 ml/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects. Based on available data, the classification criteria are not met
Carcinogenicity	: May cause cancer. Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met

CRACK SEALER PLUS BASE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure. Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met

CRACK SEALER PLUS BASE

Viscosity, kinematic	1203,70370370 mm ² /s
----------------------	----------------------------------

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
---	---

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	: Harmful to aquatic life with long lasting effects.
-----------------	--

12.2. Persistence and degradability

CRACK SEALER PLUS BASE

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

12.3. Bioaccumulative potential

CRACK SEALER PLUS BASE

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

CRACK SEALER PLUS BASE

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

12.6. Other adverse effects

Additional information	: Avoid release to the environment
------------------------	------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
--------------------------------	---

Ecology - waste materials	: Avoid release to the environment.
---------------------------	-------------------------------------

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 3082
--------------	--------

UN-No. (IMDG)	: 3082
---------------	--------

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
----------------------------	---

Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
-----------------------------	---

Transport document description (ADR)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (E)
--------------------------------------	--

Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
---------------------------------------	---

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 9
----------------------------------	-----

Danger labels (ADR)	: 9
---------------------	-----



IMDG

CRACK SEALER PLUS BASE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Transport hazard class(es) (IMDG) : 9
Danger labels (IMDG) : 9



14.4. Packing group


Packing group (ADR) : III
Packing group (IMDG) : III

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : M6
Special provisions (ADR) : 274, 335, 601
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
Hazard identification number (Kemler No.) : 90
Orange plates : 
Tunnel restriction code (ADR) : E
EAC code : 3Z

- Transport by sea

Special provisions (IMDG) : 274, 335
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP2, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

CRACK SEALER PLUS BASE

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

SDS EU (REACH Annex II)

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information provided is designed only as guidance for safe use, processing, handling, storage, transport, release and disposal. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for use in combination with any other materials or in any process, unless specified in this safety data sheet.