



## TECHNICAL DATA SHEET

# WOOD & PATIO CLEANER

ISSUE DATE: 12/3/2021 VERSION: 1.0



# SILOXOL

CLEAN • PROTECT • REPEL

Siloxol Wood & Patio Cleaner is used to kill mould, algae and lichens on outdoor surfaces, such as fences, decking and patios. This improves the cleaning process, making it quicker and more effective, avoiding the need to use regular pressure washing which can have a detrimental effect on surfaces.

## ADVANTAGES

- Kill moulds, algae and lichens quickly
- Reduces the need for power washing
- Simple to use
- Non-corrosive unlike sodium hypochlorite-based cleaners

## TYPICAL USES

- Part of cleaning process or maintenance regime for outdoor wooden structures including, but not limited to, fences, fence posts, sheds, wooden garden furniture, decking, plant containers.
- Part of cleaning process or maintenance regime for outdoor mineral substrates including, but not limited to, brickwork, concrete, stone, patio, driveways.

## SUBSTRATE PREPARATION

- Ensure substrate is dry, and weather conditions will remain dry for a minimum of 1 hour.
- Loose material should be brushed off with a stiff brush.

## APPLICATION

- Siloxol Wood & Patio Cleaner should be applied by spray, brush or roller at a coverage rate of 1 litre per 5 m<sup>2</sup>.
- Leave product for a minimum of 1 hour (ideally overnight) before cleaning off the dead mould, algae and lichens with a stiff bristled brush and water from a hose.
  - Note: Stiff bristled brush may remove paintwork

## STORAGE AND SHELF LIFE

Store in an upright position in a cool environment. Shelf life is 12 months from date of manufacture, when unopened, undamaged and stored correctly.

## HEALTH AND SAFETY

Wear appropriate person protective equipment when using product – should we copy pictograms over here?

Keep product out of reach of children and animals.

Keep unprotected persons, children, and animals away from treated surfaces until dry and clean.

For further information and advice please consult the safety data sheet available at [twistfix.co.uk](http://twistfix.co.uk), or contact the Twistfix Technical Department on +44 (0) 845 123 6006.

HSE number

**twistfix**<sup>®</sup>

Technical Department on +44 (0) 845 123 6006.