

# Total Wall Care<sup>®</sup>

## Colour Matching Tint

### DESCRIPTION

Total Wall Care Colour Matching Tint been specially developed for use on all porous, masonry surfaces. The tinting solution is vapour permeable allowing the substrate to breath.

Unlike latex and acrylic paints that coat the surface, the tinting solution stains and forms a molecular bond with the masonry. This provides a natural finish that does not change the texture or properties of the masonry.

### INSTRUCTIONS & NOTES

Shake vigorously. Inverting and rotating whilst shaking will help to remix any pigment that has settled.

Pour into a suitable vessel.

Dilute with water to achieve a slightly lighter.

A maximum ratio of 1 part Tinting Solution to 2 parts water should be used.

Tinting solution should then be applied with a clean paintbrush.

Note: Overlapping strokes may result in darker areas.

Avoid overspills. In the event of any spillage wash immediately with lots of clean water.

Note: Will stain clothing and other porous materials.

### COVERAGE

Coverage depends on the porosity of the substrate and effect required.

Determine coverage with a trial application.

Typical coverage 20-25m<sup>2</sup>/Litre - single coat.

### STORAGE

Store in a dry area, away from direct sunlight. Storage conditions should be in the range of 5°C – 25°C with low to average humidity. Average shelf life is six months in original, unopened packaging.

### SAFETY INFORMATION

#### Keep Out of Reach of Children

- Irritating to eyes and skin
- Avoid contact with eyes and skin
- Risk of serious damage to eyes
- In case of contact with eyes and skin rinse immediately with plenty of water and seek medical advice
- If swallowed seek medical advice immediately and show container.
- Gloves and eye protection should be worn during mixing and application.

Contains Potassium Silicate: 60% W/W

CAS No. 67/548/EEC