

#### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 1

Compilation date: 13/01/2015

Revision No: 8

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: FIREFOAM B2 - GUN GRADE AND HAND HELD

Product code: B2FIREGUN/HAND

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Filling, fixing and insulating gaps and cavities.

### 1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

**LEEDS** 

WEST YORKSHIRE

LS9OSW

ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: sds@everbuild.co.uk

#### 1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

#### **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Resp. Sens. 1: H334; STOT RE 2: H373; Aquatic Chronic 3: H412; Carc. 2: H351; Eye

Irrit. 2: H319; Flam. Aerosol 1: H222; Lact.: H362; Skin Irrit. 2: H315; Skin Sens. 1: H317;

-: H229; -: EUH204

Classification under CHIP: F: R11; -: R52/53; -: R64

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause harm to breast-fed children. May cause damage to organs through

prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Contains isocyanates. May produce an allergic reaction.

#### 2.2. Label elements

Label elements under CLP:

Hazard statements: H222: Extremely flammable aerosol.

#### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 2

H229: Pressurised container: May burst if heated

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351: Suspected of causing cancer.

H362: May cause harm to breast-fed children.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

EUH204: Contains isocyanates. May produce an allergic reaction.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard







Precautionary statements: P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P260: Do not breathe fumes.

P280: Wear protective gloves, eye/face protection.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P285: In case of inadequate ventilation wear respiratory protection.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P308+313: IF exposed or concerned: Get medical advice/attention.

P332+313: If skin irritation occurs: Get medical advice.

P337+313: If eye irritation persists: Get medical attention.

P342+311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

P363: Wash contaminated clothing before reuse.

P405: Store locked up.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501: Dispose of contents/container to in accordance with local/national regulations.

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 3

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

## Hazardous ingredients:

#### TRIS(2-CHLORO-1-METHYLETHYL)PHOSPHATE

		,		
EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	13674-84-5	-	Acute Tox. 4: H302	10-30%
DIMETHYL ETH	HER			
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	
PROPANE				
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
ISOBUTANE				·
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
ALKANES, C14	-17, CHLORO			
287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%

# Non-classified ingredients:

# DIPHENYLMETHANEDIISOCYANATE, ISOMERES AND HOMOLOGUES

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-079-6	32055-14-4	-	Skin Irrit. 2: H315; Resp. Sens. 1: H334; Carc. 2: H351; Skin Sens. 1: H317; Eye Irrit. 2: H319; Acute Tox. 4: H332; STOT SE 3: H335; STOT RE 2: H373	10-30%

#### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Remove/soften cured foam from skin with petroleum jelly or via constant softening with hot soapy water If symptoms persist,

consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If symptoms

persist seek medical advice.

#### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 4

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

#### 4.3. Indication of any immediate medical attention and special treatment needed

#### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers. Do not use water jet.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour

mixture. Vapour may travel considerable distance to source of ignition and flash back.

Bursting aerosols can be forcibly projected from a fire.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific

substance. Do not use equipment in clean-up procedure which may produce sparks.

Allow product to solidify and remove it by mechanical means. Remove uncured foam

with acetone Take up residues with absorbent material (e.g. sand, vermiculite). Transfer

to a closable, labelled salvage container for disposal by an appropriate method.

#### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 5

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS, Refer to section 13 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these paramaters will dramatically

reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

# Section 8: Exposure controls/personal protection

# 8.1. Control parameters

#### Hazardous ingredients:

# DIMETHYL ETHER

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m3	958 mg/m3	-	-

#### **PROPANE**

UK	1800 mg/m3	7200 mg/m3	-	-
----	------------	------------	---	---

# **ISOBUTANE**

UK 2400 mg/m3 9600 mg/m3	
--------------------------	--

# **DNEL/PNEC Values**

DNEL / PNEC No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration

is above OES or if ventilation is poor Self-contained breathing apparatus must be

available in case of emergency.

#### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 6

Hand protection: Protective gloves. Butyl gloves. Change gloves regularly to prevent permeability.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Pink

**Odour:** Characteristic odour

Solubility in water: Reacts with water.

Flash point°C: <21

#### 9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Because of the high vapour pressure, containers are liable to burst if temperature rises.

Formation of explosive gas/air mixtures.

# 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion

emits toxic fumes of hydrogen cyanide.

#### Section 11: Toxicological information

## 11.1. Information on toxicological effects

Toxicity values: No data available.

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 7

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 16 05 04

Disposal of packaging: Waste material code packaging (91/689/EEC); Council decision 2001/118/EC, O.J L47

of 16/2/2001) 15 01 10 (packaging containing residues of or contaminated by

dangerous substances)

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

#### 14.1, UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

# 14.5, Environmental hazards

Environmentally hazardous: No Marine pollutant: No

#### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 8

#### 14.6. Special precautions for user

#### **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH204: Contains isocyanates. May produce an allergic reaction.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer < state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

H362: May cause harm to breast-fed children.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that

no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R64: May cause harm to breastfed babies.

**Legend to abbreviations:** PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

### FIREFOAM B2 - GUN GRADE AND HAND HELD

Page: 9

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.